



## SCANDIPAIN PAINT REMOVER ECO

PROFESSIONAL PAINT REMOVER. REMOVES UP TO 15 LAYERS OF ALMOST ALL TYPES OF PAINT AND VARNISH FROM ALL SURFACES.

SAFE, EFFICIENT AND ENVIRONMENTALLY FRIENDLY.

### ABOUT THE PRODUCT

PAINT REMOVER ECO™ is a revolutionary paint remover that is safe for both the user, the materials and the environment. PAINT REMOVER ECO™ does not contain methylene chloride, is non-toxic, non-carcinogenic and non-caustic. This water-based paint remover effectively removes up to 15 coats of almost any coating (oil-based, water-based, acrylic, lacquer, urethane - even old lead paint) from any exterior or interior surface (wood, brick, stone, concrete, plaster, metal, plastic ), glass, fiberglass, etc.).

PAINT REMOVER ECO contains no volatile organic compounds, is odorless, user-friendly, biodegradable and pH-neutral.

### ADVANTAGES

- Removes up to 15 layers of paint in one go
- Odorless
- Water-based
- Contains no methylene chloride / harsh chemicals
- PH-level neutral
- Perfect for indoor and outdoor use

#### SCANDIPAIN GmbH & Co KG

ADDRESS Elbberg 6, DE-22 767 Hamburg, Germany. HANDELSREGISTER NR: 10 58 36, UST-ID: DE 253 77 50 65  
 TEL +49-40-85 41 43 6-0 FAX +49-40-85 41 43 6-29 WEBB [www.scandipaint.com](http://www.scandipaint.com) E-MAIL [order@scandipaint.com](mailto:order@scandipaint.com)  
 ÜBERARBEITET AM 8 september 2022 11:43 AM DRUCKDATUM 08/09/22 SEITEN 1 von 2 © SCANDIPAIN GmbH & Co KG



# SCANDIPAINT PAINT REMOVER ECO

## EASY APPLICATION AND COLOR REMOVAL

PAINT REMOVER ECO is a water-based paste that can be easily applied with a brush, roller or conventional airless sprayer. Leave the paste on the surface for 3-24 hours depending on the number of coats and the type of coating to be removed.

PAINT REMOVER PRO is formulated to stay wet and effective even without the use of SCANDIPAINT Laminated Paper. However, SCANDIPAINT Laminated Paper is required to increase exposure and is recommended for most projects.

PAINT REMOVER ECO is ideal for a variety of DIY tasks, home, commercial, professional and industrial applications. The product simplifies the paint removal process and offers top performance by removing a variety of coatings in one operation. PAINT REMOVER ECO offers users the smart solution for the most difficult paint removal projects.

## APPLICATION

**APPLY:** Put on the provided rubber gloves. Apply all 3 products in the kit (PAINT REMOVER ECO, PAINT REMOVER XTRA, PAINT REMOVER ECO 1) on an area of about 25x25cm. Apply to the correct layer thickness (about twice as thick as the coatings to be removed). Use tape to separate the samples in a grid if necessary to avoid overlapping.

**COVER:** Place the SCANDIPAINT Laminated Paper on each of the samples and lightly smooth the test area. Printed side out. Tape all edges to the substrate to protect them from rain and wind. (PAINT REMOVER ECO and PAINT REMOVER XTRA should also be tested without SCANDIPAINT Laminated Paper. SCANDIPAINT Laminated Paper increases exposure time and is critical to the success of the project, especially in hot weather).

**REMOVAL:** Allow between 6 and 24 hours before checking results. The colder the temperature the longer the exposure time, in some cases depending on the number of layers to be removed (15+) and the coating itself, more than one application may be required. That's why the test patch is so critical. Be sure to note any specific information during the test field (exposure time, temperature during the test, humidity and weather conditions during the test).

**CLEAN:** Put on rubber gloves. After a suitable exposure time, using the enclosed plastic spatula, carefully scrape under the remover and SCANDIPAINT Laminated Paper, starting at a corner. Use the spatula to gently lift up the paper, remover, and paint in one continuous motion. Once the area has been removed, immediately clean the surface (use the included Scotch Brite™ Pad or a medium nylon brush and water, high pressure hose or pressure washer). The surface should now be clean and free of paint.

The treated surface is then neutralized with the neutralizer product that is part of the packaging.

## TEST AREA

Always prepare a test area for each surface to know exactly which product to use. Here the PAINT REMOVER TEST SET is ideal! See separate test instructions. Testing before starting the project is the best way to ensure the suitability of the product. This also helps the user find out how the product is being used; the thickness of the paste that needs to be applied and the exposure time required to complete the project.

## CLEANING

**OUTDOORS:** Before cleaning, cover plants and surfaces with plastic wrap to protect against splashes and spills. Dampen the surface with clean water using a pressure washer or garden hose. Paint residues are removed with a rigid nylon brush. Pay special attention to slits, gouges and tears. Clean carefully to remove any paint residue. (For best results, a high-low pressure is recommended). Leave to dry for at least 24 hours

before neutralizing the surface. Collect and dispose of waste according to local regulations.

**INTERIOR:** Before starting work, cover / protect adjacent surfaces - including floors - with plastic film and masking tape. Use a water squirt or sponge to clean the surface with clean water. Remove any residue with a stiff nylon brush. Pay special attention to slits, gouges and tears. Clean thoroughly to remove any residue. Allow to dry for at least 12-24 hours before neutralizing the surface. Collect and dispose of waste according to local regulations.

## PROCESSING

With a brush, roller or airless device apply a layer of approx. 3-6mm (see test area result) depending on age, ambient temperature, number of layers and type of paint to be removed. Leave the product on the surface for 6-24 hours.

## PACKAGING

5 liters (4 buckets/box)  
15 liters (24 buckets/pallet)

## CONSUMPTION

PAINT REMOVER PH offers an average coverage of approx. 0.5 to 1 m<sup>2</sup> per liter. Consumption may vary. Determine exact consumption through application test.

## TECHNICAL DATA

### FLASH POINT

-

### VOLATILE ORGANIC COMPOUNDS (VOC):

0

### ODOR:

Neutral

### DENSITY:

1.1 kg

### CLEANING OF THE TOOL

Immediately after use with water.

### PROCESSING TEMPERATURE

For best results, the surface temperature should be 15°C - 35°C. The product can be used up to 2°C, but the effect will be reduced and the duration of action increased.

### STORAGE

Unopened for about 1 year, stored cool but frost-free. Opened buckets are well closed.

## SCANDIPAINT GmbH & Co KG

ADDRESS Elbberg 6, DE-22 767 Hamburg, Germany. HANDELSREGISTER NR: 10 58 36, UST-ID: DE 253 77 50 65  
TEL +49-40-85 41 43 6-0 FAX +49-40-85 41 43 6-29 WEBB www.scandipaint.com E-MAIL order@scandipaint.com  
ÜBERARBEITET AM 8 september 2022 11:43 AM DRUCKDATUM 08/09/22 SEITEN 2 von 2 © SCANDIPAINT GmbH & Co KG



# SCANDIPAIN **PAINT REMOVER ECO**

## **SAFETY**

Protect areas that will not be treated, including adjacent surfaces where spatter may occur. Plants should be protected.

NOTE: PAINT REMOVER ECO does not affect glass, aluminum or plastic surfaces.

## **HEALTH AND SAFETY REQUIREMENTS**

Do not eat. Although PAINT REMOVER ECO has been formulated to be safe for the user, the surface and the environment, applicable safety procedures should be followed at all times. Consult MSDS for important health/safety information prior to use.

## **A NOTICE**

In case of contact with skin or eyes, rinse thoroughly with water. Consult a doctor if irritation persists. Keep out of reach of children.

## **DISPOSAL**

Observe the legal regulations for disposal.



## **SCANDIPAIN GmbH & Co KG**

ADDRESS Elbberg 6, DE-22 767 Hamburg, Germany, HANDELSREGISTER NR: 10 58 36, UST-ID: DE 253 77 50 65  
TEL +49-40-85 41 43 6-0 FAX +49-40-85 41 43 6-29 WEBB [www.scandipaint.com](http://www.scandipaint.com) E-MAIL [order@scandipaint.com](mailto:order@scandipaint.com)  
ÜBERARBEITET AM 8 september 2022 11:43 AM DRUCKDATUM 08/09/22 SEITEN 3 von 2 © SCANDIPAIN GmbH & Co KG

